



Specification

Height under guides	6½" (155mm)		
Depth of throat	10¼" (260mm)		
Table Size	12½" x 12½" (320mm x 320mm)		
Table Tilt	45°		
Max. blade length and width	72⅞" x ½" (1850mm x 13mm)		
Band Wheels	11" (280mm)		
Motor	¾ H.P. x 1400 R.P.M.		
Blade Speeds			
AF186 (single speed)	see instruction book		
AF186F & AF186FM (3 speed)	Feet per min. 1160 – 2290 – 4030 Metres per min. 350 – 700 – 1225		
Table height: bench model	14½" (370mm)		
floor model	40" (1150 mm)		
Overall dimensions	<i>Height</i>	<i>Width</i>	<i>Depth</i>
AF186	33¼"	21"	15"
	845 mm	535 mm	380 mm
AF186F	34¼"	28"	15"
	870 mm	710 mm	380 mm
AF186FM	59"	28"	15"
	1500 mm	710 mm	380 mm
Net weight (approx)			
AF186	35lbs (16 kg)		
AF186F	80lbs (36 kg)		
AF186FM	119lbs (54 kg)		
Standard equipment	blade and rip fence		
Optional equipment	Mitre gauge and Startrite-Supaflex blades		

MODEL LISTING

AF186 – Bench Model less all electrical equipment but with single step pulley.

AF186F – Bench Model – 3 speeds fully motorised with ¾ H.P. motor and thermal overload starter.

AF186M – Floor Model – as AF186F, but mounted on steel cabinet base.

Some illustrations show guards removed for clarity.

Description and specifications do not form part of a contract and are subject to change without notice.

Constructional details

A quality machine of attractive design and a high standard of finish. The main components are die-cast for exceptional rigidity and vibration free operation.

The 12½" square table will tilt through 45°, has a rip fence, a depth stop and is slotted for a mitre gauge. The band wheels run on sealed for life bearings and brushes are fitted to clean sawdust from the rubber tyres. The top wheel slide is fitted with a visual blade tension indicator.

Easily adjustable blade guides and thrust rollers ensure maximum blade life. The upper guide is easily adjusted for depth and encloses the blade for additional safety.

The transmission includes a ¾ h.p. motor, vee belt and three step pulley drive providing three speeds for cutting wood, plastics and non-ferrous metals. Floor models are fitted with a closed type cabinet stand.



STARTRITE

Mar. 1977

Inca bandsaws

bench & floor type
10" throat
6 $\frac{1}{8}$ " under guides.

3 speed models cut
wood - plastics -
aluminium

